

**Product Specification**

<b>AMOTEC</b>	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	1 / 20

**Thin-Film-Transistor LCD Module  
Model:XTPQ35SN03-01**

Acceptance

Approved and Checked by

Approved by	Checked by		Made by



## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	3 / 20

### 1.General Description and Features

3.5 is a TM (Transmissive) type color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT-LCD module, a driver circuit and a back-light unit. The resolution of a 3.5" contains 320RGBx240 dots and can display up to 262K colors. The following table described the features of 3.5.

#### LCD Module

Item	Specification	Unit
Screen Size	3.5inches	Diagona
Display Resolution	320RGB(H)x240(V)	Dot
Active Area	70.08 (H) x 52.56 (V)	mm
Outline Dimension	76.9(W) x 63.4(H) x 3.3 (D)	mm
Display Mode	Normally white/Transmissive	--
Pixel Arrangement	RGB-Vertical Stripe	--
Display Color	16M	--
Gray scale inversion Direction	6 o'clock	
Viewing Direction	12 o'clock	--
Drive IC	NV3035C	--
Surface luminance	300 cd/m <sup>2</sup>	

Product Specification				
AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	4 / 20

## 2.Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	--	76.9	--	mm	--
	Vertical (V)	--	63.4	--	mm	(1)
	Thickness (T)	--	3.3	--	mm	(2)
Weight		--	N/A	--	g	--

Note (1) Not include FPC.

Refer to the Outline Dimension for further information.

(2) Back-light unit are included.

## 3.Electrical Specifications

### 3.1 Absolute Max. Ratings

#### 3.1.1 Absolute Ratings of Environment

If the operating condition exceeds the following absolute maximum ratings, the TFT LCD module may be damaged permanently.

(Ta=25±2°C, V<sub>SS</sub>=GND=0)

Item	Symbol	Min.	Max.	Unit	Note
Operating temperature	T <sub>OPR</sub>	-20	70	°C	(1)
Storage temperature	T <sub>STG</sub>	-30	80	°C	(1,2,3)

Note (1) 95 % RH Max. ( 40 °C ≥ Ta ). Maximum wet-bulb temperature at 39 °C or less.  
(Ta > 40 °C) No condensation.

Note (2) In case of below 0°, the response time of liquid crystal (LC) becomes slower and the color of panel becomes darker than normal one. Level of retardation depends on temperature, because of LC's character

Note (3) Only operation is guaranteed at operating temperature. Contrast, response time, another display quality are evaluated at +25°C.

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	5 / 20

### 3.2 Electrical Absolute Rating

#### 3.2.1 TFT-LCD Module

(Voltage Referenced to VSS)

Item	Symbol	Value		Unit	Condition
		Min.	Max.		
Digital Power Supply Voltage	VDD	VSS-0.3	5.0	V	--

#### 3.2.2 Back-Light Unit

(Ta=25±2°C)

Item	Symbol	Min.	Max.	Unit	Note
current	I <sub>f</sub>	--	30	mA	(1)
voltage	V <sub>R</sub>	--	5	V	(1)

Note (1) Permanent damage to the device may occur if maximum values are exceeded or reverse voltage is loaded. Functional operation should be restricted to the conditions described under normal operating conditions.

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	6 / 20

### 4 Electrical Characteristics

#### 4.1 Backlight Unit

The back-light system is an edge-lighting type with six white LEDs (Light Emitting Diode).

(Ta=25±2°C)

Item	Symbol	Value			Unit	Condition
		Min.	Typ.	Max.		
LED Voltage	V <sub>F</sub>	16.2	18.6	20.4	V	
LED Current	I <sub>F</sub>	-	20	-	mA	
Power Consumption	P <sub>BL</sub>	-	-	-	mW	

Note (1)  $P_{BL} = V_F \times I_F$

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	7 / 20

### 5 Input Terminal Pin Assignment

PIN.N O	SYMBOL	I/O/P	FUNCTI	MEMARK
1	LED K	P	<b>POUER GROUND</b>	
2	LED K	P	<b>POUER GROUND</b>	
3	LED A	P	<b>POUER FOR LED BACKLIHT(ANODE)</b>	
4	LED A	P	<b>POUER FOR LED BACKLIHT(ANODE)</b>	
5	NC			
6	NC			
7	NC			
8	RESET	I	Global reset pin. Active Low to enter Reset State. Suggest connecting with a RC reset circuit for stability. Normally pull high.	
9	SPENA	I	3-Wire Communication Enable. Active Low. Normally pull high. <b>Please pull high or floating under PINCTLB=0 mode.</b>	
10	SPCK	I	3-Wire Communication Clock input. Rising edge latch.	
11	SPDA	I/O	3-Wire Communication Data input/output.	
12-35	D0-D23	I	<b>DATA BUS</b>	
36	HSYNC	I	Horizontal Sync input. Default Negative polarity, can be change by HSDPOL register.	
37	VSYNC	I	Vertical Sync input. Default Negative polarity, can be change by VSDPOL register.	
38	CLK	I	Clock for Input Data. Data latched at rising/falling edge of this signal. Default positive edge latch data.	
39	NC			
40	NC			
41	VDD	P	<b>POUER SUPPLY</b>	
42	VDD	P	<b>POUER SUPPLY</b>	
43-51	NC-NC			

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	8 / 20

<b>52</b>	<b>DEN</b>	<b>I</b>	Data Input Enable. Active High to enable the data input Bus under "DE Mode". Normally pull low.	
<b>53</b>	<b>GND</b>	<b>P</b>	<b>POUER GROUND</b>	
<b>54</b>	<b>GND</b>	<b>P</b>	<b>POUER GROUND</b>	

## Product Specification

<b>AMOTEC</b>	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	9 / 20

### 6 Optical Characteristics

#### 5.1 Optical Specification

Light source: C light

Ta=25°C


Item	Symbol	Condition	Min	Typ.	Max.	Unit	Remark
<b>View Angles</b>	$\theta T$	$CR \geq 10$	30	40		Degree	Note 2 With EWW polarizer
	$\theta B$		50	60			
	$\theta L$		50	60			
	$\theta R$		50	60			
<b>Contrast Ratio</b>	CR	$\theta = 0^\circ$		350			Note3
<b>Response Time</b>	Ton	25°C		25	40	ms	Note4
	Toff						
<b>Chromaticity</b>	<b>White</b>	X	0.261	0.311	0.361		Measured by C light.
		Y	0.300	0.350	0.400		
	<b>RED</b>	X	0.586	0.636	0.686		
		Y	0.300	0.350	0.400		
	<b>GREEN</b>	X	0.261	0.311	0.361		
		Y	0.501	0.551	0.601		
	<b>BLUE</b>	X	0.084	0.134	0.184		
		Y	0.101	0.151	0.201		
<b>NTSC</b>				50		%	Note 5
<b>Transmittance</b>			6.9	7.5		%	With EWW polarizer, without DBEF

## Product Specification

<b>AMOTEC</b>	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	10 / 20

**Note 1:** Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Item	Photo Detector	Field
Contrast Ratio	SR-3	1°
Luminance		
Chromaticity		
Lum Uniformity		
Response Time	BM-7A	2°

**Note 2:** Definition of viewing angle range and measurement system.

viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).




Fig. 1 Definition of viewing angle

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	11 / 20

**Note 3:** Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$


“White state “:The state is that the LCD is driven by  $V_{\text{white}}$ .

“Black state”: The state is that the LCD is driven by  $V_{\text{black}}$ .

$V_{\text{white}}$ : To be determined       $V_{\text{black}}$ : To be determined.

**Note 4:** Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time ( $T_{\text{ON}}$ ) is the time between photo detector output intensity changed from 90% to 10%. And fall time ( $T_{\text{OFF}}$ ) is the time between photo detector output intensity changed from 10% to 90%.



**Note 5:** Definition of color chromaticity (CIE1931)


Color coordinates measured at center point of LCD.

# Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	12 / 20

## 7 Interface Timing

### Data Timing (24 bit RGB mode for 960×240 @ SEL[3:0]=1100b)



### 9.3. Specifications

Test Condition: (VCI=VCIP=3.3V, VDDA=5.0V, VSS=GND, VSSP=0V, TA=25°C)

#### 8 Bit RGB 960 CH Mode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
CLKIN frequency	Fclk	-	27	30	MHz	VDD=3.0~3.6V
CLKIN cycle time	Tclk	-	37		ns	
CLKIN pulse duty	Tcwh	40	50	60	%	Tclk
Time that HSD to 1 <sup>st</sup> data input(NTSC)	Ths	35	70	255	CLKIN	DDLY=70, Offset=0(fixed)

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	13 / 20

### 24 Bit RGB Mode (@ SEL[3:0]=1100 or 1101)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
CLKIN frequency	Fclk	6.1	6.4	8.0	MHz	VDD=3.0~3.6V
CLKIN cycle time	Tclk	125	156	164	ns	
CLKIN pulse duty	Tcwh	40	50	60	%	Tclk
Time that HSD to 1 <sup>st</sup> data input(NTSC)	Ths	40	70	255	CLKIN	DDL Y=70, Offset=0(fixed)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
<b>System Operation Timing</b>						
VDD power source slew time	T <sub>POR</sub>			1000	us	From 0V to 90% VDD
RSTB active pulse width	T <sub>RSTB</sub>	40			us	VDD=3.3V
<b>Input Output Timing</b>						
CLKIN clock time	Tclk	-		35.7	ns	Please refer to timing table(P25)
HSD to CLKIN	Thc	-	-	1	CLKIN	
HSD width	Thwh	1	-	-	CLKIN	
VSD width	Tvwh	1	-	-	Th	
HSD period time	Th	60	63.56	67	us	
VSD setup time	Tvst	12	-	-	ns	
VSD hold time	Tvhd	12	-	-	ns	
HSD setup time	Thst	12	-	-	ns	
HSD hold time	Thhd	12	-	-	ns	
Data set-up time	Tdsu	12	-	-	ns	DIN[23:0] to CLKIN
Data hold time	Tdhd	12	-	-	ns	DIN[23:0] to CLKIN
DEN setup time	Tesd	12	-		ns	DEN to CLKIN
Time that VSD to 1 <sup>st</sup> line data input	Tvs	2	13	127	Th	@CIR601/8bit RGB HV mode Control by HDLY[6:0] setting Tvs=HDLY[6:0]
Time that CCIR_V to 1 <sup>st</sup> line data input	Tvs	12	20	28	Th	@CCIR656 NTSC mode Control by HDLY[6:0] setting Tvs=HDLY[6:0]
Time that CCIR_V to 1 <sup>st</sup> line data input	Tvs	17	25	33	Th	@CCIR656 PAL mode Control by HDLY[6:0] setting Tvs=HDLY[6:0]
Time that VSD to 1 <sup>st</sup> line data input	Tvs	2	13	127	Th	@24bit RGB HV mode Control by HDLY[6:0] setting Tvs=HDLY[6:0]
Source output stable time 1	Tst	-	25	30	us	96% final, CL=30pF, RL=2K
Gate output stable time	Tgst	-	500	1000	ns	96% final, CL=40pF
VCOMOUT output stable time	Tcst	-	4	8	us	96% final, CL=33nF, RL=100ohm
<b>3-wire serial communication AC timing</b>						
Serial clock	Tspck	320	-	-	ns	
SPCK pulse duty	Tscdut	40	50	60	%	Tckh/Tspck
Serial data setup time	Tisu	120	-	-	ns	
Serial data hold time	Tihd	120	-	-	ns	
Serial clock high/low	Tssw	120	-	-	ns	
Chip select distinguish	Tcd	1	-	-	us	
SPENA to VSD	Tcv	1	-	-	us	
SPENB input setup time	Teck	150	-	-	Ns	
SPENB input hold time	Tcke	150	-	-	ns	

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	14 / 20

### 8 Reliability Condition for LCD

No change on display and in operation under the following test condition.


Condition: Unless otherwise specified, tests will be conducted under the following condition.

Temperature: 20±5°C

Humidity: 65±5%RH

Tests will be not conducted under functioning state.

No.	Parameter	Condition	Notes
1	High Temperature Operating	70°C±2°C, 240hrs (Operation state)	--
2	Low Temperature Operating	-20°C±2°C, 240hrs (Operation state)	--
3	High Temperature Storage	80°C±2°C, 240hrs	--
4	Low Temperature Storage	-30°C±2°C, 240hrs	--
5	High Temperature and High Humidity Operation Test	60°C±2°C, 90%, 240hrs	--
6	Vibration Test	Total fixed amplitude: 1.5mm Vibration Frequency: 10~55Hz One cycle 60 seconds to 3 direction of X, Y, Z each 15 minutes.	--


7.	Drop Test	<p>To be measured after dropping from 60cm high on the concrete surface in packing state.</p>  <p style="text-align: center;"><i>Concrete Surface</i></p> <p style="text-align: right;"> <i>Dropping method corner dropping</i>  <i>A corner: once</i>  <i>Edge dropping</i>  <i>B, C, D edge: once</i>  <i>Face dropping</i>  <i>E, F, G face: once</i> </p>	--
----	-----------	--	----

- Notes:
1. No dew condensation to be observed.
  2. The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.
  3. Vibration test will be conducted to the product itself without putting I in a container.

# Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	15 / 20

## 9 Dimensional outlines



日期	版本	修改内容

XIAMEN AMOTEC DISPLAY CO.,LTD

DISPLAY TYPE	TT 256K COLOR
DISPLAY RESOLUTION	320 X RGB X240
VIEWING ANGLE	12°@DC
LCD CONTROLLER/DRIVER	N7905C
LOGIC VOLTAGE	-3.3V
OPERATING TEMPERATURE	-20°C TO +70°C
STORAGE TEMPERATURE	-30°C TO +80°C
BACKLIGHT	TYPE: White COLOR: White COORDINATE: -- LED(S): -- BRIGHT VOLTAGE: --18~2V@1mA LUMINANCE(TYP): Min -- (ON THE BACKLIGHT STRAPE): Typ 2000 Max

VF=19.8V    IF=20mA

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	16 / 20

### 10 Incoming Inspection Standards

#### 11.1 VISUAL & FUNCTION INSPECTION STANDARD

##### 11.1.1 Inspection conditions

Inspection performed under the following conditions is recommended.


Temperature : 25±5°C

Humidity : 65%±10%RH


Viewing Angle : Normal viewing Angle.

Illumination: Single fluorescent lamp (300 to 700Lux)

Viewing distance:30-50cm



##### 11.1.2 Definition



Zone A : Effective Viewing Area(Character or Digit can be seen)

Zone B : Viewing Area except Zone A

Zone C : Outside (Zone A+Zone B) which can not be seen after assembly by customer .)

Note:

Product Specification				
AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	17 / 20

As a general rule ,visual defects in Zone C can be ignored when it doesn't effect product function

or appearance after assembly by customer.

### 11.1.3 Sampling Plan

According to GB/T 2828-2003 ; , normal inspection, Class II


AQL:

Major defect	Minor defect
0.65	1.5

LCD: Liquid Crystal Display , TP: Touch Panel , LCM: Liquid Crystal Module



No	Items to be inspecte d	Criteria	Classification of defects
1	Functional defects	1) No display, Open or miss line 2) Display abnormally, Short 3) Backlight no lighting, abnormal lighting. 4) TP no function	Major
2	Missing	Missing component	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed	
4	Color tone	Color unevenness, refer to limited sample	Minor
5	Soldering appearance	Good soldering , Peeling off is not allowed.	
6	LCD/Polarizer/TP	Black/White spot/line, scratch, crack, etc.	

### 11.1.4 Criteria (Visual)

Number	Items	Criteria(mm)
1.0 LCD Crack/Broken	(1) The edge of LCD broken	


## Product Specification

<b>AMOTEC</b>	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	18 / 20

<p>NOTE:</p> <p>X: Length</p> <p>Y: Width</p> <p>Z: Height</p> <p>L: Length of ITO,</p> <p>T: Height of LCD</p>			X	Y	Z			
			$\leq 3.0\text{mm}$	<Inner border line of the seal	$\leq T$			
	(2) LCD corner broken		<table border="1" style="margin: auto;"> <tr> <td style="text-align: center;">X</td> <td style="text-align: center;">Y</td> <td style="text-align: center;">Z</td> </tr> <tr> <td style="text-align: center;"><math>\leq 3.0\text{mm}</math></td> <td style="text-align: center;"><math>\leq L</math></td> <td style="text-align: center;"><math>\leq T</math></td> </tr> </table>	X	Y	Z	$\leq 3.0\text{mm}$	$\leq L$
X	Y	Z						
$\leq 3.0\text{mm}$	$\leq L$	$\leq T$						
(3) LCD crack	 <p style="text-align: center;">Crack Not allowed</p>							

## Product Specification

AMOTEC	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	19 / 20

Number	Items	Criteria (mm)																																																																				
2.0	Spot defect	<p>① light dot (LCD/TP/Polarizer black/white spot , light dot, pinhole, dent, stain)</p>  <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: center;">Zone</th> <th colspan="3" style="text-align: center;">Acceptable Qty</th> </tr> <tr> <th style="text-align: center;">Size (mm)</th> <th style="text-align: center;">A</th> <th style="text-align: center;">B</th> <th style="text-align: center;">C</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\Phi \leq 0.10</math></td> <td colspan="3" style="text-align: center;">Ignore</td> </tr> <tr> <td style="text-align: center;"><math>0.10 &lt; \Phi \leq 0.15</math></td> <td colspan="3" style="text-align: center;">3( distance <math>\geq 10\text{mm}</math>)</td> </tr> <tr> <td style="text-align: center;"><math>0.15 &lt; \Phi \leq 0.2</math></td> <td colspan="3" style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;"><math>0.2 &lt; \Phi</math></td> <td colspan="3" style="text-align: center;">0</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 10px;"><math>Y</math></p> <p style="text-align: center; margin-top: 10px;"><math>X</math></p> <p style="text-align: center; margin-top: 10px;"><math>\Phi = (X+Y)/2</math></p> <p>② Dim spot (LCD/TP/Polarizer dim dot, light leakage, dark spot)</p> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: center;">Zone</th> <th colspan="3" style="text-align: center;">Acceptable Qty</th> </tr> <tr> <th style="text-align: center;">Size (mm)</th> <th style="text-align: center;">A</th> <th style="text-align: center;">B</th> <th style="text-align: center;">C</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\Phi \leq 0.1</math></td> <td colspan="3" style="text-align: center;">Ignore</td> </tr> <tr> <td style="text-align: center;"><math>0.1 &lt; \Phi \leq 0.2</math></td> <td colspan="3" style="text-align: center;">2( distance <math>\geq 10\text{mm}</math>)</td> </tr> <tr> <td style="text-align: center;"><math>0.2 &lt; \Phi \leq 0.3</math></td> <td colspan="3" style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;"><math>\Phi &gt; 0.3</math></td> <td colspan="3" style="text-align: center;">0</td> </tr> </tbody> </table> <p>③ Polarizer accidented spot</p> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: center;">Zone</th> <th colspan="3" style="text-align: center;">Acceptable Qty</th> </tr> <tr> <th style="text-align: center;">Size (mm)</th> <th style="text-align: center;">A</th> <th style="text-align: center;">B</th> <th style="text-align: center;">C</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\Phi \leq 0.2</math></td> <td colspan="3" style="text-align: center;">Ignore</td> </tr> <tr> <td style="text-align: center;"><math>0.2 &lt; \Phi \leq 0.5</math></td> <td colspan="3" style="text-align: center;">2( distance <math>\geq 10\text{mm}</math>)</td> </tr> <tr> <td style="text-align: center;"><math>\Phi &gt; 0.5</math></td> <td colspan="3" style="text-align: center;">0</td> </tr> </tbody> </table>	Zone	Acceptable Qty			Size (mm)	A	B	C	$\Phi \leq 0.10$	Ignore			$0.10 < \Phi \leq 0.15$	3( distance $\geq 10\text{mm}$ )			$0.15 < \Phi \leq 0.2$	1			$0.2 < \Phi$	0			Zone	Acceptable Qty			Size (mm)	A	B	C	$\Phi \leq 0.1$	Ignore			$0.1 < \Phi \leq 0.2$	2( distance $\geq 10\text{mm}$ )			$0.2 < \Phi \leq 0.3$	1			$\Phi > 0.3$	0			Zone	Acceptable Qty			Size (mm)	A	B	C	$\Phi \leq 0.2$	Ignore			$0.2 < \Phi \leq 0.5$	2( distance $\geq 10\text{mm}$ )			$\Phi > 0.5$	0		
Zone	Acceptable Qty																																																																					
Size (mm)	A	B	C																																																																			
$\Phi \leq 0.10$	Ignore																																																																					
$0.10 < \Phi \leq 0.15$	3( distance $\geq 10\text{mm}$ )																																																																					
$0.15 < \Phi \leq 0.2$	1																																																																					
$0.2 < \Phi$	0																																																																					
Zone	Acceptable Qty																																																																					
Size (mm)	A	B	C																																																																			
$\Phi \leq 0.1$	Ignore																																																																					
$0.1 < \Phi \leq 0.2$	2( distance $\geq 10\text{mm}$ )																																																																					
$0.2 < \Phi \leq 0.3$	1																																																																					
$\Phi > 0.3$	0																																																																					
Zone	Acceptable Qty																																																																					
Size (mm)	A	B	C																																																																			
$\Phi \leq 0.2$	Ignore																																																																					
$0.2 < \Phi \leq 0.5$	2( distance $\geq 10\text{mm}$ )																																																																					
$\Phi > 0.5$	0																																																																					

## Product Specification

<b>AMOTEC</b>	Model: XTPQ35SN03-01	Rev. No.	Issued Date.	Page.
		A	2016,04,27	20 / 20

	Line defect (LCD/TP /Polarizer black/white line, scratch, stain)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Width(mm)</th> <th rowspan="2">Length(mm)</th> <th colspan="3">Acceptable Qty</th> </tr> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.03</math></td> <td>Ignore</td> <td colspan="3">Ignore</td> </tr> <tr> <td><math>0.03 &lt; W \leq 0.05</math></td> <td><math>L \leq 3.0</math></td> <td colspan="2"><math>N \leq 2</math></td> <td rowspan="2">Ignore</td> </tr> <tr> <td><math>0.05 &lt; W \leq 0.08</math></td> <td><math>L \leq 2.0</math></td> <td colspan="2"><math>N \leq 2</math></td> </tr> <tr> <td><math>0.08 &lt; W</math></td> <td colspan="4">Define as spot defect</td> </tr> </tbody> </table>	Width(mm)	Length(mm)	Acceptable Qty			A	B	C	$\Phi \leq 0.03$	Ignore	Ignore			$0.03 < W \leq 0.05$	$L \leq 3.0$	$N \leq 2$		Ignore	$0.05 < W \leq 0.08$	$L \leq 2.0$	$N \leq 2$		$0.08 < W$	Define as spot defect			
Width(mm)	Length(mm)	Acceptable Qty																											
		A	B	C																									
$\Phi \leq 0.03$	Ignore	Ignore																											
$0.03 < W \leq 0.05$	$L \leq 3.0$	$N \leq 2$		Ignore																									
$0.05 < W \leq 0.08$	$L \leq 2.0$	$N \leq 2$																											
$0.08 < W$	Define as spot defect																												
3.0	Polarizer B bubble	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Zone Size (mm)</th> <th colspan="3">Acceptable Qty</th> </tr> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.2</math></td> <td colspan="3">Ignore</td> </tr> <tr> <td><math>0.2 &lt; \Phi &lt; 0.4</math></td> <td colspan="3">2(distance <math>\geq 10</math>mm)</td> </tr> <tr> <td><math>0.4 &lt; \Phi &lt; 0.6</math></td> <td colspan="3">1</td> </tr> <tr> <td><math>0.6 &lt; \Phi</math></td> <td colspan="3">0</td> </tr> </tbody> </table>	Zone Size (mm)	Acceptable Qty			A	B	C	$\Phi \leq 0.2$	Ignore			$0.2 < \Phi < 0.4$	2(distance $\geq 10$ mm)			$0.4 < \Phi < 0.6$	1			$0.6 < \Phi$	0						
Zone Size (mm)	Acceptable Qty																												
	A	B	C																										
$\Phi \leq 0.2$	Ignore																												
$0.2 < \Phi < 0.4$	2(distance $\geq 10$ mm)																												
$0.4 < \Phi < 0.6$	1																												
$0.6 < \Phi$	0																												
4.0	SMT	According to IPC-A-610C class II standard . Function defect and missing part are major defect ,the others are minor defect.																											